



LaMARCHE®

THE ACCESSORY PACKAGE

OPTION 136

ALARM BOARD USED WITH 2 MSEC, STATIC TRANSFER SWITCH

Includes two form "C" relays for each status light and each of the following alarms:

Inverter available – indicates the inverter is operating within its proper range.

Load on Alternate Source – indicates the load is on the secondary source.

Load on Preferred Source – indicates the a.c. load is operating on the prime source.

Utility Available – indicates the alternate source is connected and operating within its proper range.

Phase Lock – indicates when the prime and alternate sources are in sync.

These are dry contacts which energize when the static switch "LED" lights. They are generally used if the customer wants a remote alarm.

A static load transfer switch with an approximate 2ms transfer time is available on units 1Kva and larger. This switch has no moving parts or contacts. A status light panel with 6 LED indicator lights and two switches are provided.

NOTE: Test Transfer, Auto Manual and Default Parameter contacts are provided, but are not used to indicate an alarm. See: Electronic Static Switch Option in Manual.

ECN/DATE

106 BRADROCK DRIVE
DES PLAINES, IL. 60018
(847) 299-1188
FAX:(847)299-3061

ISSUE DATE: 12329 - 9/98

INSTRUCTION DRAWING NUMBER:

P25-**LOPT136-1**